



SUNTEC GLASGOW ACTIVE MODEL LIST 2013

SUNTEC MODEL NUMBER	ROTATION/NOZZLE (FROM SHAFT END)	SPEED (RPM)	PRESSURE RANGE (PSI)	NOZZLE CAPACITY	GEAR CAPACITY	OPTIONS
A2VA3006	RH/RH	3450	100 TO 200 PSI	4 GPH @ 100 PSI 3 GPH @ 200 PSI	14.7	AVAILABLE SINGLE PACKED (SP), BULK, OR WIN/WIN PACKAGE A2VA3006N621L: 115 VOLT COIL AND 13"/6" JACKETED CORDSET
A2VA3106	RH/RH	3450	100 TO 200 PSI	4 GPH @ 100 PSI 3 GPH @ 200 PSI	14.7	AVAILABLE SINGLE PACKED (SP) OR BULK A2VA3106N621L: 115 VOLT COIL AND 13"/6" JACKETED CORDSET
A2VA7116	RH/RH	3450	100 TO 200 PSI	3 GPH @ 100 PSI 2 GPH @ 200 PSI	13.8	AVAILABLE SINGLE PACKED (SP), BULK, OR WIN/WIN PACKAGE
A2VD7119	LH/RH	3450	100 TO 200 PSI	3 GPH @ 100 PSI 2 GPH @ 200 PSI	13.8	AVAILABLE SINGLE PACKED (SP) OR BULK
A2VA7142	RH/RH	2850	100 TO 200 PSI	3 GPH @ 100 PSI	12	AVAILABLE SINGLE PACKED (SP) OR BULK
A1YD7154	LH/RH	1725	100 TO 200 PSI	7 GPH @ 100 PSI 3 GPH @ 150 PSI	12	AVAILABLE SINGLE PACKED (SP) OR BULK
A2RA7710	RH/RH OR LH	VARIABLE	VARIABLE	UP TO 2.5 GPH	4.7	NO PUMP PRESSURE RELIEF OR CUT-OFF. EXTERNAL RELIEF AND SHUT-OFF VALVE REQUIRED. WASTE OIL RECOMMENDED PUMP
A2RA7720	RH/RH	VARIABLE	VARIABLE	UP TO 2.5 GPH	7.8	NO PUMP PRESSURE RELIEF OR CUT-OFF. EXTERNAL RELIEF AND SHUT-OFF VALVE REQUIRED. WASTE OIL RECOMMENDED PUMP
A2RA7736	RH/RH	3450	100 TO 150 PSI	2.5 GPH @ 100 PSI	12.5	AVAILABLE SINGLE PACKED (SP) OR BULK WASTE OIL RECOMMENDED PUMP
A1RA7738	RH/RH	1725	100 TO 150 PSI	2.5 GPH @ 100 PSI	10	AVAILABLE SINGLE PACKED (SP) OR BULK WASTE OIL RECOMMENDED PUMP
A2RA7740	RH/RH	1725 - 3450	50 TO 65 PSI	2.5 GPH @ 100 PSI	15.2	NO PUMP PRESSURE RELIEF OR CUT-OFF. EXTERNAL RELIEF AND SHUT-OFF VALVE REQUIRED. WASTE OIL RECOMMENDED PUMP
A1YA7912	RH/RH	1725	100 TO 150 PSI	7 GPH @ 100 PSI 3 GPH @ 150 PSI	12	AVAILABLE SINGLE PACKED (SP), BULK, OR WIN/WIN PACKAGE
A1YC7914	LH/LH	1725	100 TO 150 PSI	7 GPH @ 100 PSI 3 GPH @ 150 PSI	12	AVAILABLE SINGLE PACKED (SP) OR BULK
A2YA7916	RH/RH	3450	100 TO 200 PSI	7 GPH @ 100 PSI 3 GPH @ 200 PSI	16	AVAILABLE SINGLE PACKED (SP), BULK, OR WIN/WIN PACKAGE
B2VA4006	RH/RH	3450	100 TO 200 PSI	4 GPH @ 100 PSI 3 GPH @ 200 PSI	16	AVAILABLE SINGLE PACKED (SP), BULK, OR WIN/WIN PACKAGE B2VA4006N621L: 115 VOLT COIL AND 13"/6" JACKETED CORDSET
B1VA8212	RH/RH	1725	100 TO 150 PSI	3 GPH @ 150 PSI	10	AVAILABLE SINGLE PACKED (SP) OR BULK
B2VA8241	RH/RH	3450	10 TO 20 PSI	20 GPH @ 20 PSI	29	AVAILABLE SINGLE PACKED (SP) OR BULK
B2TA8245	RH/RH	3450	200 TO 300 PSI	16 GPH @ 300 PSI	25	AVAILABLE SINGLE PACKED (SP) OR BULK
B2TA8248	RH/RH	2850 - 3450	100 TO 200 PSI	8 GPH @ 100 PSI 3 GPH @ 150 PSI	16.5	AVAILABLE SINGLE PACKED (SP) OR BULK FLOW RATES CALCULATED AT 3450 PRM
B2TA8249	RH/RH	3450	150 TO 300 PSI	18 GPH @ 150 PSI 16 GPH @ 300 PSI	25	AVAILABLE SINGLE PACKED (SP) OR BULK, SHAFT ADAPTER INCLUDED NO PUMP CUT-OFF, EXTERNAL SHUT-OFF VALVE IS REQUIRED
B2TA8260	RH/RH	3450	100 TO 200 PSI	23 GPH @ 100 PSI 15 GPH @ 200 PSI	26	AVAILABLE SINGLE PACKED (SP) OR BULK, SHAFT ADAPTER INCLUDED
B2TA8850	RH/RH	3450	100 - 200 PSI LOW FIRE 300 PSI HIGH FIRE	10 GPH @ 300 PSI	20	AVAILABLE SINGLE PACKED (SP) OR BULK, DIFFERENT VOLTAGE COILS AND CORDSETS AVAILABLE. NO PUMP CUT-OFF. EXTERNAL SHUT-OFF VALVE IS REQUIRED
B2TA8851	RH/RH	3450	100 - 200 PSI LOW FIRE 300 PSI HIGH FIRE	16 GPH @ 300 PSI	25	AVAILABLE SINGLE PACKED (SP) OR BULK, DIFFERENT VOLTAGE COILS AND CORDSETS AVAILABLE. NO PUMP CUT-OFF. EXTERNAL SHUT-OFF VALVE IS REQUIRED
B2TA8852	RH/RH	3450	100 - 200 PSI LOW FIRE 300 PSI HIGH FIRE	23 GPH @ 300 PSI	32	AVAILABLE SINGLE PACKED (SP) OR BULK, DIFFERENT VOLTAGE COILS AND CORDSETS AVAILABLE. NO PUMP CUT-OFF. EXTERNAL SHUT-OFF VALVE IS REQUIRED
B2YA8916	RH/RH	3450	100 TO 200 PSI	7 GPH @ 100 PSI 3 GPH @ 200 PSI	16	AVAILABLE SINGLE PACKED (SP), BULK, OR WIN/WIN PACKAGE
B2TA8930	RH/RH	3450	150 TO 300 PSI	25 GPH @ 150 PSI 23 GPH @ 300 PSI	32	AVAILABLE SINGLE PACKED (SP) OR BULK, SHAFT ADAPTER INCLUDED NO PUMP CUT-OFF, EXTERNAL SHUT-OFF VALVE IS REQUIRED
J4NBA1000G	RH/LH	1725	20 TO 40 PSI	26 GPH @ 40 PSI	ONLY SINGLED PIPED	AVAILABLE SINGLE PACKED (SP) OR BULK WASTE OIL RECOMMENDED
J4NBD1000G	RH/LH	1725	40 TO 80 PSI	24 GPH @ 80 PSI	ONLY SINGLED PIPED	AVAILABLE SINGLE PACKED (SP) OR BULK WASTE OIL RECOMMENDED
J4PAB1000G	RH/RH	1725 - 3450	100 TO 200 PSI	12 GPH @ 200 PSI/ 1725 44 GPH @ 200 PSI/3450	30 GPH/1725 RPM 50 GPH/2850 RPM 60 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J4PAC1000G	RH/RH	1725 - 3450	150 TO 300 PSI	2 GPH @ 300 PSI/1725 35 GPH @ 300 PSI/ 3450	30 GPH/1725 RPM 50 GPH/2850 RPM 60 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J4PAD1000G	RH/RH	1725 - 3450	40 TO 80 PSI	24 GPH @ 80 PSI/1725 57 GPH @ 80 PSI/3450	30 GPH/1725 RPM 50 GPH/2850 RPM 60 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J4PAE1000G	RH/RH	1725 - 3450	10 TO 20 PSI	28 GPH @ 20 PSI/1725 58 GPH @ 20 PSI/3450	30 GPH/1725 RPM 50 GPH/2850 RPM 60 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J4PBB1000G	RH/LH	1725 - 3450	100 TO 200 PSI	12 GPH @ 200 PSI/ 1725 44 GPH @ 200 PSI/3450	30 GPH/1725 RPM 50 GPH/2850 RPM 60 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J4PCC1000G	LH/LH	1725 - 3450	150 TO 300 PSI	2 GPH @ 300 PSI/1725 35 GPH @ 300 PSI/ 3450	30 GPH/1725 RPM 50 GPH/2850 RPM 60 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J6PAB1000G	RH/RH	1725 - 3450	100 TO 200 PSI	26 GPH @ 200 PSI/ 1725 73 GPH @ 200 PSI/3450	45 GPH/1725 RPM 75 GPH/1725 RPM 90 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J6PAC1000G	RH/RH	1725 - 3450	150 TO 300 PSI	17 GPH @ 300 PSI/ 1725 63 GPH @ 300 PSI/3450	45 GPH/1725 RPM 75 GPH/1725 RPM 90 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
J6PCC1000G	LH/LH	1725 - 3450	150 TO 300 PSI	17 GPH @ 300 PSI/ 1725 63 GPH @ 300 PSI/3450	45 GPH/1725 RPM 75 GPH/1725 RPM 90 GPH/3450 RPM	AVAILABLE SINGLE PACKED (SP) OR BULK
OTHER MODELS AVAILABLE WITH EXTENDED LEAD TIMES. PLEASE CONTACT FACTORY FOR DETAILS						
WEB SITE: WWW.SUNTECPUMPS.COM CUSTOMER PORTAL: WWW.SUNTECDIRECT.COM						
TOLL FREE CUSTOMER SERVICE 1-800-367-7116 FAX 1-270-651-9276						
LISA PARKE (MANAGER, MATERIALS AND CUSTOMER SERVICE) lparke@suntecpumps.com						
KEN SKODA(EXISTING CUSTOMER SALES)kskoda@suntecpumps.com						
XAVIER BIHR (ENGINEER, NEW PRODUCT DEVELOPMENT) xavier.bihr@suntec.fr						

